

## WOOD MOISTURE METERS

### HM9-WS Series

#### Wood moisture meter HM9-WS1 for veneer

**NEW!**

non-destructive measurement

**preselection of wood thickness: select between six different scanning depths (from 0,5 to 3 mm) - for an even more accurate measurement for low wood thickness**

21 timber groups programmed

display of wood moisture, dry density, timber group and minimum wood thickness

automatic temperature compensation

self-calibration function

display lighting

automatic switch off

battery control

8 menu languages


incl. softcase, hand strap and 4 pcs. 1,5 V AA batteries



**HM9-WS1**

#### TECHNICAL DATA

<b>Density range</b>	<b>0,175 – 1,075 g/cm<sup>3</sup> dry density</b>
<b>Scanning depth</b>	<b>0,5 - 3 mm (0,5 mm min. thickness)</b>
Menu languages	English, German, French, Spanish, Portuguese, Czech, Russian, Italian
Weight	215 g
Size (L x W x H)	150 x 73 x 23 mm
Measuring range	2 – 30 %
Operating temperature	0 – +40 °C
Storage temperature	-20 – +60 °C



As soon as the sensor plate is in contact with the surface of the wood measuring starts. The processor of the instrument analyses the sensor readings and displays the result as a percentage of moisture content in the wood.